



STRONG

SL 50/75/100 Series

超音波花邊縫合機
Ultrasonic lace sewing machine

SL系列適用於化學合成纖維布料之縫合、裁切、分條、切孔、壓花、燙金等工作

Fabrics made of artificial fiber are suitable for seaming, cutting, slitting, punching, patterning and hot stamping with SL series ultrasonic lace sewing machine.

STRONG[®]
ULTRASONIC WELDER



- 超音波可瞬間融化塑料。加工時不冒煙，不傷害布料邊緣，亦不會起毛邊。
- 花輪由特殊合金鋼料製成，焊頭耐磨損且壽命長。
- 花輪更換簡便，可依客戶所需設計各種圖樣。
- Ultrasonic melt can be down in seconds. During the processing, no smoke or spark, therefore, the fabric edge will not be damaged and there will be no burrs.
- The pattern rollers are made of special alloy steel, the welding horn is abrasion-proof with long service life.
- The rollers can be easily replaced. The rollers with different patterns can be optionally designed as requirement.

Specification SL 50/ 75/ 100 series

	SL 50	SL 75	SL 100
超音波頻率 Operating Frequency	20KHZ	20KHZ	20KHZ
輸出 Output	1200W	1400W	1400W
工作範圍 Working area	1.0~48 mm	1.0~73 mm	1.0~98 mm
空壓力需求 Drive energy	6 kg/cm ²	7 kg/cm ²	7 kg/cm ²
工作速度 Working speed	0~19 m/min	0~19 m/min	0~19 m/min
花輪尺寸 Size of roller	寬度23, 50 mm Width 23, 50 mm	寬度50, 75 mm Width 50, 75mm	寬度50, 75, 100 mm Width 50, 75, 100 mm
電源需求 Power supply	220V, 6A, 單相 220V, 6A, single phase	220V, 10A, 單相 220V, 10A, single phase	220V, 10A, 單相 220V, 10A, single phase
機械尺寸 Dimension of machine	W1200xL550xH1010 mm	W1200xL550xH1010 mm	W1200xL550xH1010 mm
驅動馬達 Driving motor	40W x 2	40W x 1, 60W x 1	40W x 1, 60W x 1
工作台尺寸 Dimension of worktable	W1200xL535xH750 mm	W1200xL535xH750 mm	W1200xL535xH750 mm
材質厚度 Thickness of material	0.03~2 mm	0.03~2 mm	0.03~2 mm
機器淨重 Net weight	130 kg	140 kg	140 kg

詳細資料歡迎來電洽詢
Additional technical information available on request.



ULTRASONIC WELDER

强榮超音波機械有限公司

STRONG ULTRASONIC MACHINERY CO., LTD.
 新北市新莊區新樹路288-21號
 No. 288-21, Xinchu Rd., Xinzhuang Dist.,
 New Taipei City 242, Taiwan
 TEL: 886-2-2203-6999 FAX: 886-2-2206-5588
 strong66@seed.net.tw strong.usonic@msa.hinet.net
 http://www.st-rong.com